

Draka EIB/KNX BUS Cable



- not to scale -

Application

EIB (European Installation Bus) cable is a special type of BUS cable suitable for use in KNX systems. EIB/KNX is a shielded bus cable which meets the requirement of “European Installation Bus” standard. It’s widely use in KNX communication for building management for lighting control, heating, air-conditioning, time management, etc.

The cable can be used in dry, wet and damp areas either inside or outside (if protected from direct sunlight)

Standards

Screened installation cable based on type J-H(ST)H according to DIN VDE 0815

LSZH: IEC60332-1, IEC 61034-2, IEC 60754-1/2

Construction

Conductor	Bare Copper Wire, 0.5mm ²		Ø 0.80mm
Insulation	PE		Ø1.6mm
Color code	a-conductor	b-conductor	
Pair 1	Red	Black	
Pair 2	Yellow	White	
Stranding	2 conductors to a pair		
Cable Lay up	1 or 2 pairs to the core		
Wrapping	1 x PET Foil		
Overall Screen	Aluminum Polyester Foil (Coverage 100%)		Overlapping ≥ 25%
Drain Wire	Tinned Copper Drain Wire 0.4mm ²		Ø 0.71mm
Rip Cord	Yes		
Sheath	LSZH		Ø7.6 ± 0.5 mm
Sheath color	Green (RAL 6018)		

Mechanical Properties

Min. Bend Radius (Without Load)	4 x OD
Min. Bend Radius (With Load)	8 x OD
Operating Temperature	-25°C to 70°C
Min. Installation Temperature	-5°C to 60°C

Electrical Properties

Max. Cond. Resistance DC @ 20°C	37.5 Ω /km
Insulation Resistance (at 500V, 1min.)	10 G Ω *km
Nom. Capacitance Conductor to Conductor	60pF/m
Inductance	0.65mH/km
Voltage Rating	300V
AC Test Voltage (1 min)	4000 V

Ordering Information

UC Part Number	SAP1C	Description	P.U
EIB2P0.8L-GN	60081652	Draka EIB BUS Cable 2PR x 0.8mm BC Shielded LSZH Green	500m/reel

Marking:

Marked in 1 meter intervals with inkjet printing as follows:

Draka EIB BUS CABLE <Part Number> <Pair Qty>P <XX>MM BC Shielded LSZH <FC> <BATCH CODE> <XXX>M

<XX>: denotes conductor size in MM

<FC> : Draka defined factory Code

<BATCHCODE>: Factory defined tracking code MM/YYYY or WW/YYYY

<XXX> : increasing length marking by 1metre

Logistic

Packing:

Wooden drum with protection

Delivery lengths:

Standard delivery length is 500m per drum \pm 5%.

Enquiries

Please contact our local sales office or email to: mms.asia@prysmiangroup.com

Multimedia Solutions is the data communication portfolio of Prysmian Group and comprises all the necessary portfolio of cable solutions for data communication.

Ask about UC CONNECT for a complete Structure Cabling Solutions with 25 Years System Warranty.

Visit www.drakauc.com for more information.

© PRYSMIAN GROUP 2022, All Rights Reserved

All sizes and values without tolerances are reference values. Specifications are for product as supplied by Prysmian Group: any modification or alteration afterwards of product may give different result.

The information contained within this document must not be copied, reprinted or reproduced in any form, either wholly or in part, without the written consent of Prysmian Group. The information is believed to be correct at the time of issue. Prysmian Group reserves the right to amend this specification without prior notice. This specification is not contractually valid unless specifically authorised by Prysmian Group.