


## Draka UC Dual Boot Copper Patch Cord

Cat.6a U/FTP UNSHIELDED 26AWG 500 MHz, Stranded



(Only for reference)

### Application

Generic cabling systems

Primary (Campus), Secondary (Riser), Tertiary (Horizontal)

IEEE 802.3: 10Base-T; 100Base-T; 1000Base-T; 10GBase-T

IEEE 802.5 16 MB; ISDN; TPDDI; ATM

IEEE 802.3af (PoE); IEEE 802.3at (PoE+)

### Standards

ANSI/TIA 568.2-D

ISO/IEC 11801-1/2

EN 50173

IEC 61935-2

IEC 60603-7

### Construction

Item	
<b>Conductor</b>	
Size	26AWG
Type	Stranded bare copper
Diameter	7/0.16±0.01 mm
<b>Insulation</b>	
Type	Foam PE
Diameter(Nom)	1.03±0.05 mm
Thickness(Nom)	0.26±0.05 mm
<b>Pairs</b>	

Color	Blue/White, Orange/White, Green/White, Brown/White
<b>Shield</b>	
Individual shield	Aluminum Polyester Tape with PET bonded inside, Individual Pair Screen
Individual shield thickness	0.065mm
<b>Jacket</b>	
Type	LSZH
Overall Diameter(Nom)	6.0±0.3 mm
Thickness(Nom)	0.50±0.05 mm
<b>Assembly</b>	
RJ45 Modular Plug	50 u'' gold plated contact
Termination Coding	TIA 568-B
Plug Housing	UL94V-0 rated clear polycarbonate
Boot	Unique dual boot design to maximize cable latch protection
<b>Performance</b>	
Component Level	1m-10m
<b>Bend radius</b>	
With Load	≥ 8 x O. D
No Load	≥ 8 x O. D
<b>Temperature range</b>	
During operation	-20°C to +60°C
During installation	0°C to +50°C
During storage	-20°C to +60°C

## Fire Rating

LSZH IEC 60332-1; IEC 60754-1&2; IEC 61034-2

## Ordering Information

The PN of the Dual Boot Cat.6a U/FTP unshielded LSZH are configured based on the table below:

PATCHCORD	PATCHCORD TYPE	COLOR		LENGTH
PC	XXXX	XX	-	yy
	8720 – Dual Boot Cat.6a U/FTP unshielded LSZH	GN – Green BL – Blue WH - White		1 = 1m 0 = 1.5m 2 = 2m 3 = 3m 5 = 5m 10 = 10m

Example of a Dual Boot copper patch cord part number:

**PC8720GN-1:** Dual Boot copper patch cord Cat.6a U/FTP unshielded LSZH in 1-metre length with green color

UC Part Number	SAP1C	Description	Weight (g)	Packaging
PC8720GN-yy	...	DRAKA UCONNECT CAT.6a DBOOT PATCH CORD UFTP UNSHIELDED LSZH 26AWG yyM GREEN	...	1 pc / bag
PC8720BL-yy	...	DRAKA UCONNECT CAT.6a DBOOT PATCH CORD UFTP UNSHIELDED LSZH 26AWG yyM BLUE	...	1 pc / bag
PC8720WH-yy	...	DRAKA UCONNECT CAT.6a DBOOT PATCH CORD UFTP UNSHIELDED LSZH 26AWG yyM WHITE	...	1 pc / bag

\*yy=length:1=1m, 2=2m, 10=10m; M=meter

## Marking:

Marked in 1-meter intervals as follows:

**Draka UCONNECT DBOOT Cat.6a U/FTP UNSHIELDED LSZH <UC Part Number> 26AWG EN 50288 ISO/IEC 11801 2nd ed. WW/YYYY <Batch Code> <FC>**

<UC PART NUMBER>: Cable part number

<WW/YYYY>: Week/Year

<BATCH CODE>: Factory defined tracking code

<FC>: Draka defined factory Code

Marking size: 3.0±0.5 mm, Marking color: White on black sheath, black on other color sheath

## Enquiries

---

Please contact our local sales office or email to: [mms.asia@prysmiangroup.com](mailto:mms.asia@prysmiangroup.com)

Multimedia Solutions is the data communication portfolio of Prysmian Group and comprises all the necessary portfolio of cable solutions for data communication.

Ask about UC CONNECT for a complete Structured Cabling Solutions with 25 Years System Warranty.

Visit [www.drakauc.com](http://www.drakauc.com) for more information.

---

© PRYSMIAN GROUP 2022, All Rights Reserved

All sizes and values without tolerances are reference values. Specifications are for product as supplied by Prysmian Group: any modification or alteration afterwards of product may give different result.

The information contained within this document must not be copied, reprinted or reproduced in any form, either wholly or in part, without the written consent of Prysmian Group. The information is believed to be correct at the time of issue. Prysmian Group reserves the right to amend this specification without prior notice. This specification is not contractually valid unless specifically authorised by Prysmian Group.